

1. (Canceled)
2. (Currently amended) ~~The computer system of claim 1,~~ A computing system for scalably managing annotations, the computing system comprising:
 - a tier III server for storing annotations;
 - a tier II server for storing an index of the annotations stored on the tier III server, but not the annotations, that is separate and distinct from the tier III server; and, wherein the tier II server further stores a plurality of generic properties for the annotations; and
 - a tier I server for determining if a content source has an index of the annotations stored on the tier II server that is separate and distinct from the tier II and tier III servers.
3. (Currently amended) ~~The computerized system of claim 1,~~ A computing system for scalably managing annotations, the computing system comprising:
 - a tier III server for storing annotations, wherein the tier III server further stores one or more type specific properties for the annotations;
 - a tier II server for storing an index of the annotations stored on the tier III server, but not the annotations, that is separate and distinct from the tier III server; and
 - a tier I server for determining if a content source has an index of the annotations stored on the tier II server that is separate and distinct from the tier II and tier III servers.
- 4-6. (Canceled)
7. (Currently amended) ~~The computing system of claim 1,~~ A computing system for scalably managing annotations, the computing system comprising:
 - a tier III server for storing annotations, wherein the tier III server further stores client software to allow a user to view a type of annotation;

a tier II server for storing an index of the annotations stored on the tier III server, but not the annotations, that is separate and distinct from the tier III server; and

a tier I server for determining if a content source has an index of the annotations stored on the tier II server that is separate and distinct from the tier II and tier III servers.

8-9. (Canceled)

10. (Previously presented) A scalable computerized method of posting an annotation, the method comprising:

sending an annotation post from a client to a tier III server;

storing a portion of the annotation post on the tier III server;

sending a second portion of the annotation post from the tier III server to a tier II server that is separate and distinct from the tier III server;

storing the second portion of the annotation post on the tier II server;

sending association information from the tier II server to a tier I server that is separate and distinct from the tier II and tier III servers; and

storing the association information on the tier I server.

11. (Original) The computerized method of claim 10, wherein the acts are performed in the order listed.

12. (Original) The computerized method of claim 10, further comprising notifying the client of a successful post to the tier III server.

13. (Original) The computerized method of claim 12, wherein notifying the client occurs prior to sending the second portion of the annotation to the tier II server.

14. (Original) The computerized method of claim 12, further comprising notifying the tier III server of a successful post to the tier II server.

15. (Original) The computerized method of claim 14, further comprising notifying the tier II server of a successful post to the tier I server.

16. (Original) The computerized method of claim 15, wherein sending the annotation post from the client to the tier III server comprises sending a URL for the tier I server, a URL for the tier II server, a URL for the tier III server, a context document identifier, type specific annotation properties, generic annotation properties, and an annotation body.

17. (Original) The computerized method of claim 16, wherein storing a portion of the annotation on the tier III server comprises storing the annotation body and the type specific annotation properties.

18. (Original) The computerized method of claim 17, further comprising generating a unique identifier for the annotation body and type specific annotation properties stored on the tier III server.

19. (Original) The computerized method of claim 18, wherein sending a second portion of the annotation to the tier II server comprises sending a URL for the tier I server, a URL for the tier II server, a URL for the tier III server, a context document identifier, generic annotation properties, and the unique identifier.

20. (Original) The computerized method of claim 19, wherein storing the second portion of the annotation on the tier II server comprises storing the generic annotation properties, the URL for the tier III server, and the unique identifier.

21. (Original) The computerized system of claim 20, wherein sending association information to the tier I server comprises sending the tier I server URL, the tier II server URL, the context document identifier and an indexing identifier.

22. (Previously presented) A computer-readable medium having stored thereon a "client-to-tier III server" data structure for scalable annotations, comprising:

a first field containing data representing a context document identifier;
a second field containing data representing a body of the annotation;
a third field containing data representing generic properties of the annotation;
a fourth field containing data representing type specific properties of the annotation;
a fifth field containing data representing a URL for a tier III server for receiving and storing a portion of the post of the annotation;

a sixth field containing data representing a URL for a tier II server for receiving and storing a portion of the post of the annotation wherein the URL for the tier II server is distinct from the URL for the tier III server; and

a seventh field containing data representing a URL for a tier I server for receiving and storing associations for the annotation, wherein the URL for the tier I server is distinct from the URLs for the tier II and tier III servers.

23. (Previously presented) A computer-readable medium having stored thereon a "tier III server-to-tier II server" data structure for scalable annotations, comprising:

a first field containing data representing a context document identifier;
a second field containing data representing generic properties of the annotation;
a third field containing data representing a URL for a tier III server for receiving and storing a portion of the post of the annotation;

a fourth field containing data representing an identifier for the portion of the post of the annotation stored on the tier III server;

a fifth field containing data representing a URL for a tier II server for receiving and storing a portion of the post of the annotation wherein the URL for the tier II server is distinct from the URL for the tier III server; and

a sixth field containing data representing a URL for a tier I server for receiving and storing associations for the annotation, wherein the URL for the tier I server is distinct from the URLs for the tier II and tier III servers.

24. (Previously presented) A computer-readable medium having stored thereon a "tier II server-to-tier I[[]] server" data structure for scalable annotations, comprising:

- a first field containing data representing a context document identifier;
- a second field containing data representing an indexing identifier of the annotation;
- a third field containing data representing a URL for a tier II server for indexing the annotation; and

- a fourth field containing data representing a URL for a tier I server for receiving and storing associations for the annotation, wherein the URL for the tier I server is distinct from the URL for the tier II server.

25. (Previously presented) A scalable computerized method for managing annotations, the method comprising:

- storing within a tier I server reference to a tier II server storing an index that identifies a tier III server that stores an annotation associated with a content source;

- storing within a tier II server that is separate and distinct from the tier I server an index that identifies the tier III server that stores an annotation associated with a content source;

- storing within a tier III server that is separate and distinct from the tier I and tier II servers the annotation associated with a content source;

- receiving by the tier I server from a client a document identifier that identifies the content source; and

providing a first response to the client from the tier I server, wherein the first response comprises one or more associations for the document identifier and a reference to a tier II server for each of the associations.

26. (Previously presented) The method of claim 25, further comprising:
receiving by the tier II server from the client a selection identifying one of the associations for the document identifier;

providing a second response to the client from the tier II server, wherein the second response comprises a header for each of the annotations associated with the document identifier and the reference to the tier III server for each annotation.

27. (Previously presented) The method of claim 26, further comprising:
receiving by the tier III server from the client a request for the annotation; and
providing a third response to the client from the tier III server, wherein the third response comprises.

28. (Previously presented) The computerized method of claim 27, wherein the document identifier is selected from the group consisting of a uniform resource locator, a file name, and a directory path.